

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2000-351940
(43)Date of publication of application : 19.12.2000

(51)Int.Cl. C09D183/04
B05D 7/24
B65D 83/00
C09D 5/00
C09D 5/16
C09D127/12
C09D129/10
C09D143/04

(21)Application number : 11-162818

(71)Applicant : JSR CORP

(22)Date of filing : 09.06.1999

(72)Inventor : KANAMORI TARO
SHIMIZU TATSUYA
SAKAGAMI TOSHIKI

(54) COATING COMPOSITION FOR SPRAYING, AEROSOL CAN AND FORMATION OF COATING MEMBRANE

(57)Abstract:

PROBLEM TO BE SOLVED: To obtain the subject coating composition for spraying that sprays a photocatalyst to impart antifouling properties to a variety of parts in house hold appliances and internal finishing materials by spraying a mixture of a specific organosilane or the like, water and/or an organic solvent and a photocatalyst.

SOLUTION: This coating composition comprises (A) at least one selected from an organosilane of the formula: $(R_1)_nSi(OR_2)_4-n$ (R_1 is a 1-8C monovalent organic group, R_2 is a 1-5C alkyl, a 1-6C acyl; n is 0-2), its hydrolyzates and condensates (methyltrisiloxane or the like), (B) water and/or an organic solvent, for example, i-propyl alcohol or the like, and (C) a photocatalyst, for example, TiO_2 or the like. In a preferred embodiment, the amount of water to be used is about 0.7-2 moles per mole of the structural unit represented by the formula: $(R_1)_nSi(OR_2)_4-n$, while the amount of the component C is 5-400 pts.wt. on the solid basis, per 100 pts.wt. of the structural unit represented by the formula: $(R_1)_nSi(OR_2)_4-n/2$ in the component A.

LEGAL STATUS

[Date of request for examination] 22.11.2005

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]